Master PICS, TD #3: Vector waves, elasticity, PML

Vincent Laude

December 16, 2020

1 Static deformation of a silicon beam

Consider a silicon beam clamped on the left side. The beam is 10 microns long and 500 nm thick. We neglect in a first approximation the third dimension and we want to analyze the bending of the beam under the action of gravity: given its small mass and its rigidity, by how much does it bend naturally?

- 1. Study and understand script static.edp. What equation is implemented? What are the material constants and how are then defined? What are the boundary conditions?
- 2. Run the script and observe the output. How is the deformed mesh obtained?



Figure 1: Static deformation of a silicon beam under gravity.

2 Modes of deformation of a silicon beam

We consider again the same silicon beam. We now want to obtain the possible modes of deformation and their frequencies.

- 1. Study and understand script modes.edp. Which equation is now solved and how is it different from the previous one? Why do we have modes deforming in-plane and others only along the third dimension?
- 2. Run the script and observe the different modal shapes. Play with the scaling factor to animate the deformed mesh.
- 3. Change the boundary condition to: all free. Run again and discuss the changes?
- 4. Change the boundary condition to: left and right clamped. Run again and discuss the changes?

3 Phononic crystal slab in silicon

We consider a thin membrane in silicon. When processed to form a periodic array of holes (or inclusions), a phononic crystal slab is formed (see Figure 2).

- 1. Study and understand script bs_slab.edp and the various files it includes. What is different from the band structure scripts given in TD1?
- 2. Run the script and observe how the mesh is defined (it can be rotated in the 3D view). Note: This is a fully featured script used to generate band structures in publications. *It is complicated.*



Figure 2: (a) Examples of FEM meshes for the periodic unit-cell of a phononic crystal slab. (b) Band structure of a square lattice phononic crystal slab of circular holes in silicon (d/a = 0.9).

4 PML for acoustic waves

We come back to the finite 2D phononic crystal considered in TD1 (question 2). We will replace the radiation boundary condition by a perfectly matched layer surrounding the computation domain. The case of the circularly symmetric PML is considered, because it is well suited for radiation problems.

- 1. Compare script src2d_source.edp with script acoustic_source_radiation.edp of TD1. What is different and what is not?
- 2. Consider script phononic_crystal.edp that was given as a solution to TD1 (a crystal of 7×4 steel rods). Can you write a script that replaces the radiation boundary condition with the same PML as above?



Figure 3: PML for an acoustic wave incident on a small finite phononic crystal of steel rods in water.